

- 5 a) a filter bag adapted to be received in the catch basin for capturing the solids which enter the catch basin through [the] an inlet of the catch basin, said bag having an open top adapted to be positioned at the catch basin inlet, a closed bottom and bag sidewalls; [and]
- 10 b) a plurality of elongated lift flaps each having a first end and a second end joining the top of the bag and adapted to extend across [the] sidewalls of the catch basin [sidewalls] at the catch basin inlet, loops defined in the flaps away from the bag and spaced openings intermediate either end of each flap in the loops, each of said loops adapted to receive a lift rod;
- 15 and
- c) a plurality of lift rods of sufficient length extended into the loops in the flaps so that portions of the rods are exposed at the openings for attachment to lift members, whereby portions of the flaps between the filter bag and the
- 20 loops are adapted to extend between the grate and the catch basin inlet so that the grate sandwiches the flaps in place against the catch basin and the flaps support the bag in the catch basin.

~~2~~ SUB D1 > 25. (Amended) The ~~catch basin filter~~ of claim [22] 23, wherein the filter bag is ~~formed of a woven material~~.

- 10 30. (Amended) A method of installing a catch basin filter in a catch basin, the catch basin comprising:
- an inlet through which water and solids flow into the catch basin, an outlet through which water flows out of the catch basin, wherein the inlet is positioned above the outlet, and a
- 5

- 2 -

9  
FAX COPY RECEIVED

MAR 29 1996

GROUP 1300

↓  
plurality of basin sidewalls, each sidewall having an upper end at the inlet and a recess located at the upper end, the sidewalls defining a chamber, the grate located on the top of the basin inlet and having grate sides positioned in the recesses, and the  
10 filter comprising:

○3  
a filter bag having an open top, a closed bottom and one or more sidewalls extending between the top and the bottom of the bag; and

a flap joining the top of each [of the sidewalls]  
15 sidewall, said method comprising the steps of:

placing the filter bag in the catch basin so that each of the bag sidewalls are adjacent to the catch basin sidewalls and the filter bag open top is positioned above the filter bag closed bottom;

20 placing [the] each of the filter bag flaps into the recess of the upper end of the catch basin; and

sandwiching each of the filter bag flaps between the top of the basin and the grate sides, thereby holding the bag in place.

---

Please add claims 33-34.

---

1  
--33.13 A catch basin filter for use with a catch basin and a grate, wherein the catch basin filter includes:

c4  
5 a) a filter bag adapted to be received in the catch basin filter for capturing the solids which enter the catch basin through an inlet of the catch basin, said bag having a  
↓  
rectangularly shaped open top adapted to be positioned at the catch basin inlet, a closed bottom and four tapered bag

- 3 -

FAX COPY RECEIVED  
MAR 29 1996  
GROUP 1300